

| Paramount <i>LFFR-PVC</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010 |               |                             |                    |
|--|---------------|-----------------------------|--------------------|
| Size (sq mm)   | Configuration | Std. pack of coil in carton | Rate per 90 meters |
| 0.75   | 24/0.2        | 22                          | 875                |
| 1  | 14/0.3        | 16                          | 1210               |
| 1.5  | 22/0.3        | 12                          | 1740               |
| 2.5  | 50/0.25       | 8                           | 2825               |
| 4  | 56/0.3        | 6                           | 4280               |
| 6  | 84/0.3        | 4                           | 6305               |

| Paramount <i>LFFR</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010 |               |      |                |                      |               |
|---|---------------|------|----------------|----------------------|---------------|
| Size (sq mm)  | Configuration | Amps | Rate per meter | Coil Length in meter | Rate per Coil |
| 0.5   | 16/0.2        | 5    | 6.58           | 180                  | 1185          |
| 0.75  | 24/0.2        | 8    | 9.44           | 180                  | 1700          |
| 1   | 32/0.2        | 13   | 12.17          | 180                  | 2190          |
| 1.5   | 30/0.25       | 17   | 17.81          | 180                  | 3205          |
| 2.5   | 50/0.25       | 24   | 28.83          | 180                  | 5190          |
| 4   | 56/0.3        | 30   | 45.69          | 180                  | 8225          |
| 6   | 84/0.3        | 38   | 67.31          | 180                  | 12115         |
| 10  | 140/0.3       | 52   | 115.75         | 100                  | 11575         |
| 16  | 126/0.4       | 70   | 184.00         | 100                  | 18400         |
| 25  | 196/0.4       | 88   | 285.85         | 100                  | 28585         |
| 35  | 276/0.4       | 112  | 400.20         | 100                  | 40020         |
| 50  | 396/0.4       | 146  | 573.75         | 100                  | 57375         |
| 70  | 360/0.5       | 216  | 835.05         | 100                  | 83505         |
| 95  | 480/0.5       | 262  | 1082.25        | 100                  | 108225        |
| 120   | 608/0.5       | 310  | 1380.20        | 100                  | 138020        |
| 150   | 750/0.5       | 355  | 1721.70        | 100                  | 172170        |
| 185   | 931/0.5       | 415  | 2095.80        | 100                  | 209580        |
| 240   | 1200/0.5      | 500  | 2771.85        | 100                  | 277185        |
| 300   | 1500/0.5      | 550  | 3460.95        | 100                  | 346095        |
| 400   | 2013/0.5      | 590  | 4561.45        | 100                  | 456145        |
| 500   | 2562/0.5      | 660  | 5782.45        | 100                  | 578245        |
| 630   | 3416/0.5      | 725  | 7719.65        | 100                  | 771965        |

| Paramount <i>FRLS/HRFR/ZHLS</i> Insulated unsheathed single core bright electrolytic annealed bare copper conductor flexible house wire for working voltage up-to and including 1100 volts, as per IS-694 : 2010 |               |                      |       |       |           |
|--|---------------|----------------------|-------|-------|-----------|
| Size (sq mm)   | Configuration | Coil Length in meter | FRLS  | HRFR  | ZHLS/HFRF |
| 0.75   | 24/0.2        | 180                  | 1810  | 1935  | 2220      |
| 1  | 32/0.2        | 180                  | 2370  | 2490  | 2890      |
| 1.5  | 30/0.25       | 180                  | 3360  | 3540  | 4030      |
| 2.5  | 50/0.25       | 180                  | 5645  | 6075  | 6620      |
| 4  | 56/0.3        | 180                  | 8870  | 9275  | 9830      |
| 6  | 84/0.3        | 180                  | 12710 | 13240 | 13980     |
| 10   | 140/0.3       | 100                  | 12400 | 12965 | 13995     |
| 16   | 126/0.4       | 100                  | 19755 | 20395 | 21875     |
| 25   | 196/0.4       | 100                  | 30260 | 31250 | 33465     |
| 35   | 276/0.4       | 100                  | 42295 | 43640 | 46515     |

| Paramount <i>SOLAR CABLE-XLPO</i> Insulated and sheathed single core bright electrolytic annealed Tinned copper conductor flexible Solar Cable for working voltage up-to and including 1000 volts AC / 1800 volts DC, as per BSEN 50618 |               |                     |
|---|---------------|---------------------|
| Size (sq mm)  | Configuration | Rate per 100 meters |
| 2.5   | 50/0.25       | 4785                |
| 4   | 56/0.3        | 6905                |
| 6   | 84/0.3        | 9650                |
| 10  | 140/0.3       | 15755               |
| 16  | 126/0.4       | 23905               |

**Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

| Size (sq mm) | 2 core             | 3 core             | 4 core             |
|--------------|--------------------|--------------------|--------------------|
|              | Rate per 100 meter | Rate per 100 meter | Rate per 100 meter |
| 0.5          | 2030               | 2650               | 3340               |
| 0.75         | 2660               | 3550               | 4495               |
| 1            | 3340               | 4510               | 5795               |
| 1.5          | 4485               | 6105               | 7995               |
| 2.5          | 7085               | 9760               | 12650              |
| 4            | 10820              | 15115              | 19715              |
| 6            | 15785              | 22150              | 29100              |
| 10           | 26085              | 37065              | 48480              |
| 16           | 41920              | 58935              | 77415              |
| 25           | 62140              | 89790              | 118400             |
| 35           | 86575              | 124395             | 164195             |

**Paramount Flat Three Core PVC / XLPE Insulated industrial power cables for Submersible Pumps for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

| Size (sq mm) | 3 core PVC          | 3 core XLPE         |
|--------------|---------------------|---------------------|
|              | Rate Per 1000 meter | Rate Per 1000 meter |
| 1            | 45095               | 46315               |
| 1.5          | 64240               | 65395               |
| 2.5          | 101050              | 102610              |
| 4            | 147520              | 150230              |
| 6            | 214720              | 218115              |
| *8           | 295655              | 297210              |
| 10           | 359080              | 362420              |
| 16           | 571980              | 568185              |
| 25           | 874920              | 873000              |
| 35           | 1206735             | 1208980             |

**Paramount PVC Insulated sheathed multi core bright electrolytic annealed bare copper conductor flexible industrial power cables for working voltage up-to and including 1100 volts, as per IS-694 : 2010**

| SIZE | 5 Core | 6 Core | 7 Core | 8 Core | 10 Core | 12 Core | 14 Core | 16 Core | 19 Core | 24 Core |
|------|--------|--------|--------|--------|---------|---------|---------|---------|---------|---------|
| 0.5  | 4220   | 5050   | 5500   | 6700   | 8220    | 9450    | 10930   | 12390   | 14335   | 18660   |
| 0.75 | 5740   | 6985   | 7675   | 9130   | 11385   | 13160   | 15085   | 17300   | 20085   | 26010   |
| 1    | 7595   | 9105   | 10030  | 11950  | 14895   | 17260   | 19820   | 22705   | 26605   | 34420   |
| 1.5  | 10325  | 12375  | 13750  | 16445  | 20335   | 23690   | 27460   | 31250   | 36675   | 47315   |
| 2.5  | 16325  | 19785  | 22080  | 26275  | 32740   | 38285   | 44140   | 50510   | 59065   | 76035   |
| 4    | 25490  | ....   | ....   | ....   | ....    | ....    | ....    | ....    | ....    | ....    |

These cables shall be manufactured generally conforming to IS 694. Standard length : 500 m +/- 5% in non returnable wooden drums. Non standard lengths may be supplied at our discretion upto 20% of the order quantity.

\*Cable in XLPE insulation and size 8 Sq mm will not bear any ISI mark on the cable and drums.

**Terms & Conditions:**

- 1.The above rates are exclusive of GST which shall be charged extra at actual.
- 2.Freight: Inclusive above order value 2,00,000 INR & extra up to order value 2,00,000 INR
- 3.This Price List is subject to change without prior notice.
- 4.As per international practice which is also adopted by BIS, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
5. This price list supersedes our previous list.